

PRODUCT DESCRIPTION

Polyflash is a heavy-duty, pressure sensitive tape that combines a strong polyester backing with an elastomeric, modified butyl rubber adhesive that provides an instant watertight bond on most surfaces. Aggressive tack assures a positive instant seal and maximum surface contact. It will conform to surface variations and irregular areas.

USAGE/PURPOSE

- Metal roof seams
- HVACs
- Vents
- Gutters
- Ducts
- Valleys
- Chimneys
- Asphalt roofing
- Flashings
- Piping
- Mobile homes
- Truck/trailer roofs
- Walls
- Skylights
- Stacks
- Interior/exterior use

FEATURES & BENEFITS

- Forms an instant, watertight seal, allowing it to be installed quickly and with the threat of inclement weather conditions
- Is able to be manipulated to conform to irregular shapes for convenient application procedure

PACK SIZE

- 100mm x 15m roll
- 12 rolls per carton

TYPICAL PHYSICAL PROPERTIES

Adhesion	Excellent
Application Temperature	0°C - 45°C
Flexibility	Excellent
Solids by Weight	100% with no evaporation
Bond Time	Immediate tack, full bond within 24 hours
Elongation	75%


NOTE: Typical physical properties should not be used as specifications.

SUBSTRATE PREPARATION

Surface must be dry, clean and free from all dirt, debris, dust and foreign matter which could prevent proper adhesion. This is best accomplished using a high pressure wash of at least 2,000 psi. Oily surfaces must be cleaned with a surface cleaner. All surfaces must be completely dry prior to the application of Polyflash tape. Polyflash can be directly applied to clean metal or glass without the use of a primer.

PRECAUTIONS

Apply at temperatures over 0°C. Surfaces must be clean and free of moisture and foreign contamination. A remote trace of moisture will seriously affect adhesion. Polyflash must be topcoated the same day it is applied for protection from UV degeneration in exterior appliances.



METHOD OF APPLICATION

Cut desired length of Polyflash with scissors or knife. Peel release liner from back and simply press into place. Press firmly by hand or with small wallpaper-type roller to ensure complete adhesion. Be sure edges are tight.

MAINTENANCE

The Polyflash application should be checked on a regular schedule with additional inspections after the system has been exposed to severe weather conditions. Small area touch up can be made at any time by following recommended application procedures.

HEALTH & SAFETY PRECAUTIONS

The Safety Data Sheet (SDS) must be read and understood prior to use.

TECHNICAL SERVICE

Tremco CPG Australia Pty Ltd has a team of Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

Tremco CPG Australia Pty Ltd products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG Australia written instructions and (b) in any application recommended by Tremco CPG Australia, but which is proved to be defective, will be replaced free of charge.

Any information provided by Tremco CPG Australia in this document in relation to Tremco CPG Australia's goods or their use is given in good faith and is believed by Tremco CPG Australia to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. Tremco CPG Australia makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

CONTACT OUR TEAM

Tremco CPG Australia Pty Ltd
 ABN: 25 000 024 064
 Unit 12, 4 Southridge Street
 Eastern Creek, NSW 2766
 P: (02) 9638 2755
 F: (02) 9638 2955
 E: tremco@tremco.com.au