

EUCO QWIKSTITCH

Fast Curing Concrete Repair Mortar

**Traffic In
Under An
Hour!**

Product Overview

EUCO QWIKstitch is a two component hybrid urethane repair liquid used to mend cracks in concrete, repair spalled joints, and patch damaged or uneven concrete surfaces. Its fast cure time makes quick work of repair jobs; concrete repaired with **QWIKstitch can be opened to heavy traffic in less than one hour.**

QWIKstitch is an ultra-low viscosity material formulated to penetrate deep into cracks, structurally mending them back together. For larger repairs, QWIKstitch can be mixed with aggregate to make a tough mortar perfect for quickly filling patches or repairing pop-outs and spalls.

In just **10 minutes**, QWIKstitch produces a tough polymer concrete repair ready for traffic that will stay in place under the toughest conditions.



Features & Benefits

- Can be applied neat, or at a range of thicknesses with blended aggregate.
- Very fast cure time.
- Can be opened to traffic in as little as 30 minutes
- Wide application range: -18°C to 43°C
- Low VOC and no solvent odour
- No priming required
- Can be used for concrete & asphalt repairs

Typical Applications

- Repair of industrial floors & walkways
- Cracked concrete surfaces
- Spalled, or damaged floor joints
- Parking structures and concrete bridge repairs
- Airport runway & taxiway repairs
- Cold Room floor & entrance repairs



EUCLID CHEMICAL

Typical Physical Properties At 24°C

Property	Standard	Result
Compressive Strength (Mortar)	ASTM C579B	
1.5 Hours		27.9MPa
24 Hours		42.5MPa
7 Days		49MPa +
Compressive Strength (Neat Resins)	ASTM D695	
1.5 Hours		31.7MPa
24 Hours		34.8MPa
Shore D Hardness	ASTM D2240	70
Tensile Strength: 7 Days	ASTM D638	23.5MPa
Tensile Elongation	ASTM D638	16.3%
Bond Strength	ASTM C882	13.1MPa
Water Absorption	ASTM D570	0.25%
Gel time / Working time		2 to 3 minutes
Tack Free Time		10 minutes
Cure Time		30 minutes
Viscosity		60 cps
VOC Content		19g/L
Colour: Part A		Clear / Amber
Part B		Black
Mixed		Gray

COMPLIMENTARY PRODUCTS:

- **EUCO QWIKJOINT UVR** – UV Resistant Polyurea Semi-rigid floor joint filler for construction / control joints
- **DYMONIC 100** – High performance, one part polyurethane joint sealant for expansion joints.

SERVICE AND SUPPORT:

Simon Ross
 National Business Development
 Manager – Grouts & Repairs
 T. 1800 318 038
simon.ross@tremco.com.au

Tremco Construction Products Group (CPG) represents the combined power of brands including Nudura, Willseal, and Tremco, along with Tremco CPG affiliates Flowcrete, illbruck, Nullifire and Euclid Chemical.

